



Product Facts

Memprochem 2200 Reverse Osmosis Silica Inhibitor

GENERAL PRODUCT INFORMATION.

Memprochem 2200 is a multifunctional antiscalant for reverse osmosis systems, highly effective in preventing silica scale formation on membrane surfaces.

Besides its excellent silica scale inhibition properties Memprochem 2200 is effectively controlling calcium carbonate, strontium sulphate, barium sulphate, iron oxide and calcium fluoride scale formation.

All ingredients in Memprochem 2200 are certified to ANS/NSF Standard 60 for use in reverse osmosis systems producing potable water.

Physical and Chemical Product Properties.

The following are typical properties for Memprochem 2200 and should not be regarded as specification limits for the product. A product specification is available on request.

- Appearance : Clear white to pale yellow
- Odour : Slight

Packaging Information.

Memprochem 2200 is available in various packages.

Chemical Reactivity.

Memprochem 2200 is not affected by chlorine or other oxidising biocides under normal conditions of use. Memprochem 2200 should be injected in membrane systems after chlorine and sodium metabisulphite treatment. Memprochem 2200 is not compatible with residual cationic monomers from the pre-treatment.

Application and Dosage Level.

Memprochem 2200 is an aqueous solution of organic acids and is corrosive in its concentrated form. Corrosion resistant dosing equipment must therefore be used. Examples of suitable materials are PVC, glass reinforced plastic or HDPE.

Recommended injection point is into the feedwater downstream of any filtration equipment and cartridge filters.

Memprochem 2200 is miscible with water in all proportions. It may be applied as the neat product, or as a solution in permeate water. A minimum dosing solution strength of 10% w/w is recommended. Memprochem 2200 should be dosed continuously, and proportionately to the feed water flow, to maintain the recommended dosage level.

The dosage level required is dependent on the quality of the feed water and the saturation indices of the various scale forming species present in the concentrated brine.

Recommended operation limits of the most relevant brine water parameters:

- Silica : up to 240 ppm
- LSI : (+)2-(+)2.5.

Dose level projection and optimal system recovery recommendations are available on request.

Important Note : Over and under-dosing may cause membrane fouling so please contact your local Zion Enviro Systems representative to define the optimal feed point and dosage rate.

Maximum Dilution.

Maximum dilution is temperature related as shown below.

Temperature, °C	Maximum Dilution. %
<30	10
30-35	25
>35	50

Dealer / Distributor

